

## X<sup>4</sup> Bulk X-ray Inspection Systems

## www.loma.com

Versatile, proven X-ray detection for the food and packaging industries



- Versatile Models and reject systems to suit a wide range of loose bulk flow product
- Easy to use Intuitive full colour touch-screen
- Sensitive Auto calibration, which requires no programming and maximizes performance
- Fast Typical throughput in excess of 10T/hr without loss in performance
- Reliable Heavy duty conveyor components, built for 24/7 operation



## X-ray Inspection Systems

Finish: 304 stainless steel with brushed finish

Typical Line Height: 900mm ± 50mm

Typical System Length: 2500mm

Belt Width: 300/500/600mm

Supply Voltages: 230/1ph/50Hz N+E or 110/1ph/60Hz N+E

Air Supply: 5 to 8 bar

Reject Options: Single or Multilane lift or drop flap

Environment: IP 55

Belt Type: Flat (food quality) belt

Standard Inclusions: Quick release belt, Height adjustable feet, Image and

report archiving, Hinged interlocked covers, Variable

speed

Options: Reject confirmation, Bin full sensing, Reject bin, Survey

meter, Remote diagnostics, Lockable wheels, LomaEnet,

Modem, Washdown

## **Technical Specification**

Industrial Grade PC with modem, Ethernet and front access USB port

Embedded Windows XP operating system

Digitally controlled WASC (Wide Angle, Self Cooled) high performance X-ray tank. (Tube life estimated at 7 to 10 years)

Unique USB high speed, high stability, detector array with 0.8mm diode pitch

Computer vision system utilising image processing and morphological techniques

Pass Key protected set-up

USB Report and image archiving

Full diagnostic and system health monitoring with date and time stamp archiving, including remote support tools

Usage monitoring with planned maintenance prompts

Modular system with speed digital communications between major components

Loma Systems, Summit Ave, Southwood, Farnborough, Hampshire, GU14 0NY





